



## WOCA EXTERIOR OIL SYSTEM – Specification Sheet for

### cladding / decking applied on site

#### **Product description:**

WOCA Exterior Oil systems are based on environmental friendly products. Vegetable oil components, water, hardener, UV-absorber, water repellent substances, and fungicides produces the optimal results on cladding enabling easy and simple maintenance. The system is based on WOCA Exterior Cleaner and WOCA Exterior Oil.

The product has a solid matter content approx. 30%, has exceptional impregnation properties, and produces a strong and water resistant surface. The oil impregnates the wood structure and protects the surface from within.

WOCA's philosophy is that wood in itself is a unique and a natural material, which possesses a number of natural inner properties needed to ensure long lasting durability. These qualities/properties only need to be strengthened and stimulated, so the wood stays in the same condition as the day it was installed.

#### **Product Properties:**

- ✓ Based on renewable vegetable oils
- ✓ Built in UV Filter
- ✓ Fast drying
- ✓ Easy to apply
- ✓ Penetrating / None Film building

#### **Competitive advantages:**

- ✓ Environmentally friendly formula
- ✓ Sustainable and renewable raw material
- ✓ Doesn't flake off

#### **Value to the client:**

- ✓ Durable and long lasting results
- ✓ Easy & effective maintenance
- ✓ Healthy environment
- ✓ No sanding between treatments required



<b>Area of application:</b>
Surface treatment of timber cladding
<b>Special requirements:</b>
<p>Do not over coat the substrate without removing excess material</p> <p>Do not apply the material in direct sun light</p> <p>Optimal working temperature: between 15°C &amp; 30°C (diverting from these instructions may cause unintended results)</p> <p>Maximum moisture allowed is: 14-17%</p> <p>ACCOYA® and other softwoods, with the exception of Western Red Cedar are primed with WOCA Outdoor Primer prior to the Oil treatment</p>
<b>Disclaimer &amp; Warning:</b>
<p>Always remember to test on a small area in order to check the surface and the compatibility of the product. Different batch numbers are recommended always to let mix before application to ensure optimal uniform result of treatment.</p> <p>WoodCare Denmark accepts no responsibility for unintended use, damage or injury resulting from this product because of failure to follow the appropriate instructions.</p> <p><b>Warning:</b> <i>Risk of self-ignition: Due to the risk of self-ignition, it is important that sanding dust and oil-wetted rags or paper towels etc. are soaked in water and disposed of in a tightly closed container after use!</i></p>

<b>Technical Data: WOCA Outdoor Primer</b>	
Consumption:	Approx. 50-100g/m <sup>2</sup>
PH-value:	7-8
Specific gravity (gr/cm):	1.0gr/cm
Viscosity:	12-15"/4
Solid matter content:	Approx. 12%
Drying times:	Touch dry after 2-4 hours / ready for first application of oil after 4-6 hours.
Flash Point:	>100° C.
Shelf life:	3 years in unopened condition
Colour:	Yellowish in wet condition
Gloss:	Matt
Transportation & Storage:	Frost proof and avoid direct sunlight
Application:	Industrial as well as manual
Danger label:	No classification – none solvent based (VOC content: max 30g/1000g)
Safety:	Observe Safety Data Sheet and work accordingly
Packaging:	Standard 2,5L and 20L on demand



<b>Technical Data: WOCA Exterior Oil</b>	
Coverage:	8-12m <sup>2</sup> /liter depending on the type of wood and application type
PH-value:	7-8
Specific gravity (gr/cm <sup>3</sup> ):	1.0gr/cm <sup>3</sup>
Viscosity:	16-20"/4
Solid matter content:	Approx. 30%
Drying times:	Touch dry after 2-4 hours / ready for next application next day / fully hardened after 5-7 days.
Flash Point:	>100° C.
Shelf life:	3 years in unopened condition
Colour:	Yellowish in wet condition
Gloss:	Matt
Transportation & Storage:	Frost proof and avoid direct sunlight
Application:	Industrial as well as manual
Danger label:	No classification – not solvent based (VOC content: max 50g/1000g)
Safety:	Observe Safety Data Sheet and work accordingly
Packaging:	0,75L, 2,5L and 20L
Available:	Natural, Teak, Black, Grey, Walnut, Bankirai, Larch, Anthracite, White, Red Brown, Olive, Silver as well as custom colours on demand.

<b>Application:</b>	
<u>Preparation:</u>	Timber surface must be free from sanding dust, grease etc. This system is also suitable for rough sawn or band sawn material.
<u>First application:</u>	<p>Apply <b>WOCA Outdoor Primer</b> with a paintbrush or the WOCA Exterior Oil Applicator in an even layer (<i>Can be tinted if necessary. Ask for WOCA for advice on how to do</i>) Application done on all sides including the end grain.</p> <p>Do not leave any excess material before final drying of wood surface. Any excess material is removed with rags.</p> <p>Leave the wood to dry. (12-24H at 20°C). Surface should not feel sticky before next treatment.</p>
<u>Second application:</u>	Apply WOCA Exterior Oil with paintbrush or the WOCA Exterior Oil Applicator in an even layer. Application done on all sides including the end grain. Remove any excess material with rags. Leave the wood to dry over night for drying. (12-24H at 20°C). Wood should not feel sticky before final application.



<p><u>Third application:</u></p>	<p>Apply a thin final coat of WOCA Exterior Oil with a paintbrush or the WOCA Exterior Oil Applicator. Apply it in a thin layer and remove excess oil with rags if necessary.</p> <p>ATTENTION! – If timber cladding boards are supplied in random or fixed length, and are to be docked/recut onsite to size, apply and seal WOCA OUTDOOR RPIMER by brush etc. in an even layer on the end grain to avoid water ingress and protect timber against occasional mould growth.</p>
<p>Cleaning tools:</p>	<p>Hot water and soap</p>
<p>Occasional Maintenance:</p>	<p><i>Depending on exposure and wear, the surface requires maintenance. In general, it is good policy to refresh the surface once a year or when required.</i></p> <p>Typically between 12-36 months depending on:</p> <ul style="list-style-type: none"> <li>- the chosen colour</li> <li>- horizontal surface versus vertical surface             <ul style="list-style-type: none"> <li>- direction of exposure North, East, West or South</li> </ul> </li> </ul> <p>Clean the surface using WOCA Exterior Cleaner mixed with water in a ratio of 1:2. Clean the surface with a stiff nylon brush or with the WOCA Silicium brush. Hose down the dirty rinsing solution and leave surface to dry for 4-6 hours. After drying the WOCA Exterior Oil is applied as the above mentioned installation treatment.</p> <p>Frequency: the surface is inspected every 6-12 months and cleaned and re-oiled accordingly.</p> <p><b><i>When regular maintenance regime is conducted, no sanding will be needed between treatments!</i></b></p>
<p>Custom Maintenance Regime:</p>	<p>WOCA offers customized maintenance regimes if requested. This allows local weather and traffic exposure to be taken into the equation.</p>
<p>On-line support:</p>	<p>Please also study all the educational how-to-do-videos on: <a href="http://www.wocadenmark.com/video">www.wocadenmark.com/video</a></p>
<p>Old wood:</p>	<p>The wood is thoroughly cleaned with one of the WOCA Exterior Cleaning products depending on the wear and tear.</p> <p>Any old finish is sanded off until bare wood is achieved</p>



**Safety:** Please study all WOCA Material Safety Data Sheets on-line at:  
<http://www.wocadenmark.com/download/safety-data-sheets>

**Other:**

Please study additional inspirational material at:

- ✓ <http://www.wocadenmark.com/download/brochures>
- ✓ <http://www.wocadenmark.com/architects>
- ✓ [http://issuu.com/woodcaredenmark/docs/woca\\_imagebrochure\\_uk](http://issuu.com/woodcaredenmark/docs/woca_imagebrochure_uk)

**CONTACT:**

**WOCA Denmark**  
WoodCare Denmark A/S  
Tvaervej 6  
DK-6640 Lunderskov  
Office: +45 99 58 56 00  
E-mail: [info@twoodcare.com](mailto:info@twoodcare.com)  
Web.: [www.wocadenmark.com](http://www.wocadenmark.com)

**WOCA Australia PTY**  
PO BOX 99,  
Port Melbourne, VIC 3207  
Australia  
Office: 1 800 337 477 / Fax: 03 9646 4535  
[Kurt Beyer Mobile: 0412 746 970](mailto:kurt@wocaus.com.au)  
[kurt@wocaus.com.au](mailto:kurt@wocaus.com.au)  
[www.wocaus.com.au](http://www.wocaus.com.au)