

# SPAX Decking screw - cylindrical head



- T-STAR plus with recess T25 prevents the bit from slipping and ensures an ideal distribution of force.



- The fixing thread permits a safe and permanent connection of the wood parts.



- The small cylinder head can easily be countersunk in the timber with reduced splitting of the material, providing an impeccable visual appearance.



- CUT point Effectively reduces splitting of the wood.

- SPAX typical ground serrations. For quick and secure fastening.

- Pre-drilling We recommend pre-drilling for hardwoods.



## Applications

- Decking, face fix for cladding.



Step 1: Drill the boards and substructure with a SPAX Step drill. Use the complete length of the drill. Use the highest possible speed (around 3,000 rpm).



Step 2: Drive the decking screw straight in with a T-STAR plus T25 BIT. Drive it in without stopping until the head is flush.



Result: Impeccable visual appearance and low splitting effect when sinking the cylinder head. Safe connection due to fixing thread.

| SPAX D Decking Screw<br>Countersunk |  | Max. Timber Thickness | Product Code  | SPAX T-STAR plus Drive Bit<br>(50mm Long) | Drive Bit Product Code |
|-------------------------------------|--|-----------------------|---------------|---|------------------------|
| Decking                             | Up to 45mm                                   |                       |               |   |                        |
| Cladding                            | Face fix for Cladding                        |                       |               |   |                        |
| Usage                               | Top fix for Decking<br>Face fix for Cladding |                       |               |   |                        |
| Screw Sizes                         | 5 x 40                                       | 12mm                  | 0537000500403 | T-25                                      | 5000009183209          |
|                                     | 5 x 50 Hardwood Joists Only                  | 19mm                  | 0537000500503 | T-25                                      | 5000009183209          |
|                                     | 5 x 60 19mm Decking on Pine Joists           | 24mm                  | 0537000500603 | T-25                                      | 5000009183209          |
|                                     | 5 x 70                                       | 28mm                  | 0537000500703 | T-25                                      | 5000009183209          |
|                                     | 5 x 80                                       | 32mm                  | 0537000500803 | T-25                                      | 5000009183209          |
|                                     | 6 x 100                                      | 42mm                  | 0538000601003 | T-25                                      | 5000009183309          |
|                                     | 8 x 120 Boardwalk Screw                      | 45mm                  | 0538000801205 | T-40                                      | 5000009183259          |
| Tools To Use                        | SPAX 4mm Step Drill                          |                       | 5000009186540 |   |                        |
|                                     | SPAX 4mm Replacement Drill Bit               |                       | 5000009185004 |   |                        |