

Technical Data Sheet

End Grain Seal

Product Description

Product Type
Area of Application

Water-based, quick drying and easy to apply end grain seal.
Transparent moisture protection for end grain areas of wooden windows and doors.
Recoatible with ZOBEL water-based paint systems.

Technical Data

Base of Binder
Color
Density
Viscosity

Acrylate-Polyurethane system
Colorless
Ca. 1,03 g/ml
Ca. 11 seconds (DIN-4-Cup / 20 °C)

Processing Instructions

Application Method
Processing Viscosity
Processing conditions

Brushing
Ready to use. Check viscosity. If necessary, can be thinned with water
Apply with a soft brush:
- Substrate must be dry and free of dust and grease
- Moisture content of the wood ca. 13 %
- Ca. 20 °C for substrate, material und environment, ca. 50% relative air humidity
- Do not process below 15 °C or more than 30 °C
- Stir material before use; avoid inclusion of air

Product Consumption
Drying Time
(20 °C / 50% relative air humidity)

Ca. 80 ml/m²
Can be worked over after ca. 40 minutes.
Drying time depends on applied quantity and ambient conditions. Low temperature and high humidity retard drying. Always ensure adequate temperature and air exchange.
Immediately after use with water or Zowo-Clean Hydro Cleaner

Cleaning of the tools

Additional Information

VOC-Labeling
Minimum Shelf-Life
Safety Instructions

EU-limit for the product (Cat. A/e): 150 g/l (2007) / 130 g/l (2010)
This product contains maximum < 130 g/l VOC
12 months cool but free of frost in the closed original packaging
Always read label and product information before use. Please observe the usual precautions during processing and storage. For safety-relevant data and instructions on disposal refer to the Material Safety Data Sheet.